



RESTAGRO

www.restagro.com.tr

TYRE PRODUCT CATALOG



RESTAGRO

**TYRE
PRODUCT
CATALOG**



www.restagro.com.tr



STORY

Restagro Group, with its sensitive approach to production and supply in line with developing global technology, provides quality services in the fields of Agricultural Machinery, Pivot Irrigation Systems, and Spare Parts. While providing one of the world's leading marketing and product logistics networks, it establishes strong relationships with growers and parts suppliers.

We have strong relationships at every stage of the supply chain. Utilizing our world-class marketing, storage, and logistics network, including bulk storage systems and container packaging facilities,

we serve our customers in the production of a wide range of spare parts in the field of Agricultural Machinery and Irrigation equipment and spare parts (including agricultural wheels, construction machinery wheels, spraying machines, and combine harvester group spare parts).

As Restagro Group, we are proud to make positive social, environmental, and economic contributions to the regions and countries where we operate. We are committed to strong corporate, quality, and governance policies and practices, which are fundamental to the long-term success of our business.

We are honored to supply agricultural irrigation machinery, equipment, and spare parts to all corners of the world. We take pride in the support we provide to our customers near and far, as well as to the communities where we live and work. With our expert team in sales, service, and spare parts, we are focused on meeting the needs of all our customers.

www.restagro.com.tr





Tractor Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
12.4-36	12	1464	315	W11	1925	330	MR-1
12.4-38	12	1514	315	W11	1905	310	MR-1
13.6-16	8	1000	345	W12	1060	150	MR-1
13.6-20	8	1060	345	W12	1400	160	MR-1
14.9-24	10	1265	378	W13	1990	230	MR-1
14.9-38	14	1621	378	W13	2725	320	MR-1
15.5-38	10	1570	395	W14	2320	230	MR-1
18.4-30	12	1550	467	W16L	3180	230	MR-1
18.4-34	12	1655	467	W16L	3375	230	MR-1
20.8-34	12	1735	528	W18L	3785	200	MR-1
20.8-42	12	1935	528	W18L	3750	190	MR-1
23.1-30	14	1705	587	DW20	4200	200	MR-1
24.5-32	16	1803	622	DW21	4500	210	MR-1
30.5L-32	16	1819	775	DW27	5000	180	MR-1



Irrigation Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
13.6-24	10	1210	345	W12	1790	250	R-1
14.9-24	10	1265	378	W13	1990	230	R-1
14.9-24	10	1265	378	W13	1990	230	RST-6
11.2-38	10	1465	285	W10	1555	300	R-1



Tractor Tyre



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
5.00-12	8	590	145	4.00E	345	280	R-1
5.50-17	6	750	138	4.00E	400	280	R-1
6.00-12	8	640	165	4.50E	450	330	R-1
6.00-14	8	690	165	4.50E	530	330	R-1
6.00-16	8	745	165	4.50E	550	360	R-1
6.50-16	8	765	180	5.00F	660	330	R-1
7.50-16	8	810	205	5.50F	770	280	R-1
7.50-20	8	910	205	5.50F	915	280	R-1
8.30-20	8	895	210	W7	850	310	R-1
8.3-24	8	995	210	W7	830	250	R-1
8.5-20	8	875	195	W7	780	250	R-1
9.5-16	6	860	240	W8	800	210	R-1
9.5-20	8	950	240	W8	955	280	R-1
9.5-24	8	1050	240	W8	1110	280	R-1
9.5-28	8	1140	240	W8	1185	280	R-1
9.5-32	8	1250	240	W8	1260	280	R-1
11.2-20	8	1005	285	W10	1085	240	R-1
11.2-24	10	1105	285	W10	1380	300	R-1
11.2-28	8	1205	285	W10	1305	240	R-1
11-32	6	1360	305	W10	1000	140	R-1
12.4-24	10	1160	315	W11	1640	290	R-1
12.4-28	8	1260	315	W11	1510	230	R-1
13.6/12-38	10	1565	345	W11	2215	250	R-1
13.6-24	10	1210	345	W12	1790	250	R-1
13.6-28	10	1310	345	W12	1910	250	R-1
14.9-26	10	1315	378	W13	2055	230	R-1
14.9-28	10	1365	378	W13	2120	230	R-1
14.9-30	10	1415	378	W13	2190	230	R-1
15-24	10	1330	410	DW14	2800	280	R-1
16.9-24	10	1335	430	W15L	2230	200	R-1
16.9-28	10	1435	430	W15L	2380	200	R-1
16.9-30	12	1485	430	W15L	2730	240	R-1
16.9-34	10	1585	430	W15L	2605	200	R-1
16.9-38	10	1685	429	W15L	2760	200	R-1
18.4-26	12	1450	467	DW16	2985	230	R-1
18.4-38	12	1755	467	W16L	3575	230	R-1
20.8-38	12	1835	528	W18L	4000	200	R-1
23.1-26	12	1605	587	DW20	3610	170	R-1



Tractor Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
9.5-24	8	1120	285	W8	1100	280	R-2
12.4-24	8	1192	315	W11	1285	220	R-2
13.6-24	10	1210	350	W12	1910	250	R-2
14.9-24	8	1305	378	W13	1600	180	R-2
14.9-28	8	1406	378	W13	1700	180	R-2
18.4-30	10	1550	467	W16L	2500	180	R-2
18.4-34	10	1655	467	W16L	2725	180	R-2
18.4-38	10	1755	467	W16L	2900	180	R-2
20.8-38	12	1887	528	W18L	4000	200	R-2
23.1-26	16	1605	587	DW20	3750	220	R-2
23.1-30	16	1829	610	DW20	4000	225	R-2
23.1-34	12	1850	590	DW20	4500	225	R-2
24.5-32	16	1862	622	DW21	3560	140	R-2



Paddy Field Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
19.5L-24	12	1383	495	W17	2145	210	R-2
23.1-26	12	1662	587	DW20	3610	170	R-2
28L-26	14	1672	715	DW25	4745	170	R-2
18L-24	6	1304	445	DW15L	1340	230	R-2
20L-24	6	1382	495	DW16	1340	230	R-2
16L-24	4	1140	406	W14	644	230	R-2



Paddy Field Tyre



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-12	6	690	160	4.50E	425	270	PR-1
6.00-14	6	710	165	4.50E	450	250	PR-1
6.50-16	6	830	165	5.00F	565	250	PR-1
7.50-16	6	890	195	5.50F	750	300	PR-1
8.3-20	8	950	210	W7	1130	350	PR-1
8.3-24	8	1050	210	W7	1275	330	PR-1
9.5-24	8	1150	240	W8	1475	290	PR-1
11.2-24	10	1205	285	W10	1800	310	PR-1
11-32	10	1460	305	W10	1400	250	PR-1
12.4-24	8	1245	315	W11	1980	230	PR-1
12.4-28	6	1315	315	W11	1785	200	PR-1
13.6-24	10	1246	345	W12	1790	250	PR-1
13.6-38	10	1710	345	W12	2780	250	PR-1
14.9-24	10	1410	378	W13	1990	230	PR-1
14.9-26	10	1460	378	W13	2040	230	PR-1
14.9-28	10	1510	378	W13	2150	230	PR-1
14.9-30	10	1560	378	W13	2190	230	PR-1
16.9-28	12	1533	430	W15L	2540	230	PR-1
16.9-30	10	1585	430	W15L	2455	200	PR-1
16.9-34	10	1685	430	W15L	3385	220	PR-1
18.4-30	12	1597	467	W16L	3180	230	PR-1
18.4-38	12	1855	467	W16L	3575	180	PR-1
20.8-38	12	1972	528	W18L	4100	200	PR-1



F-2(4RIB)



F-2(3RIB)



RST-657



F2-3



I-1

Tractor Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
10.00-16	10	910	275	W8L	1325	340	F-2(4RIB)
11.00-16	10	970	315	W10L	1485	310	F-2(4RIB)
4.00-12	4	535	110	3.00D	250	340	F-2(3RIB)
4.00-14	6	590	110	3.0DD	315	450	F-2(3RIB)
5.00-15	6	665	140	4J	465	420	F-2(3RIB)
5.50-16	6	710	150	4.00E	525	370	F-2(3RIB)
6.00-16	8	740	16v0	4.00E	675	450	F-2(3RIB)
6.50-16	8	760	175	4.50E	735	420	F-2(3RIB)
6.50-20	8	860	180	5.00F	865	420	F-2(3RIB)
7.5L-15	8	745	208	6LB	840	370	F-2(3RIB)
7.50-16	8	810	205	5.50F	870	370	F-2(3RIB)
7.50-18	8	860	205	5.50F	945	370	F-2(3RIB)
7.50-20	8	910	205	5.50F	1020	370	F-2(3RIB)
9.00-16	8	860	235	6LB	1080	310	F-2(3RIB)
9.5L-15	8	780	240	8LB	930	310	F-2(3RIB)
11L-15	8	810	280	8LB	1070	280	F-2(3RIB)
10.00-16	10	910	275	W8L	1325	340	F-2(3RIB)
11.00-16	10	970	315	W10L	1485	310	F-2(3RIB)
5.50-16	8	685	150	4.00E	625	420	RST-657
6.00-16	8	740	160	4.00E	675	450	RST-657-1
9.00-16	12	894	276	6LB	1245	390	F2-3
11L-14	8	750	280	8LB	1120	250	I-1
11L-15	8	775	280	W8L	1130	220	I-1
11L-16	12	803	279	W8L	1510	360	I-1
9.5L-15	8	780	240	8LB	1120	300	I-1
12.L-15	12	823	318	10	1750	360	I-1
6.00-16	6	710	158	4.00E	685	275	I-1
7.50-16	10	785	203	5.50F	1240	400	I-1
10.5/80-18	10	885	274	9	1935	370	I-1



Implement Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
7.00-12	12	683	192	5.00F	1050	390	IMP100
10.0/80-12	8	715	264	9	1240	310	IMP100
10.0/75-15.3	10	765	264	9	1525	390	IMP100
11.5/80-15.3	12	854	290	9	2145	410	IMP100
12.5/80-15.3	14	869	297	9	1650	430	IMP100
12.5/80-18	14	985	308	9	2900	425	IMP100
400/60-15.5	16	874	404	13	3725	380	I-3
500/45-22.5	16	1022	503	16	2360	280	I-3
500/50-17	14	950	500	16	4125	480	I-3
400/60-15.5	16	874	404	13	2240	400	RIB100
16.5/70-18	14	1065	425	E13	3650	410	RST-101
6.50-16	10	760	182	4.50E	975	530	RST-672
7.00-16	12	790	202	5.5	1090	530	RST-672-1
26*7.5-12	4	680	205	5.50F	370	180	RST-900



IMP100



I-3



RIB100



RST-672



RST-900



RST-101

OTR TYRE



(Off-The-Road) Tyre

E3/L3(W1)

E3/L3(W2)

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)		Inflated Pressure (kpa)		Pattern
					10 km/h	50 km/h	10 km/h	50 km/h	
7.50-16	10	805	215	6.00/G	860	/	530	/	E3/L3(W1)
9.00-16	14	890	255	6.5H	1120	/	260	/	E3/L3(W1)
12.00-16	16	840	240	6.50H	1705	/	680	/	E3/L3(W1)
16/70-20	16	1075	410	13	5600	3350	450	350	E3/L3(W1)
16/70-24	16	1175	410	13	5600	3350	450	350	E3/L3(W1)
20.5/70-16	16	1075	410	8.50H	/	2850	/	350	E3/L3(W1)
15.5-25	16	1275	395	12.00/1.3	6750	3850	525	325	E3/L3(W1/W2)
17.5-25	16	1350	445	14.00/1.5	7300	4250	475	300	E3/L3(W1/W2)
17.5-25	20	1350	445	14.00/1.5	8250	5000	575	400	E3/L3(W1/W2)
20.5-25	20	1490	520	17.00/2.0	9500	6000	450	325	E3/L3(W1/W2)
20.5-25	24	1490	520	17.00/2.0	10300	6700	525	400	E3/L3(W1/W2)
23.5-25	20	1615	595	19.50/2.5	10900	7300	375	300	E3/L3(W1/W2)
23.5-25	24	1615	595	19.50/2.5	12500	8000	475	350	E3/L3(W1/W2)
26.5-25	24	1750	675	22.00/3.0	14000	9250	400	300	E3/L3(W1/W2)
26.5-25	28	1750	675	22.00/3.0	15500	10000	475	350	E3/L3(W1/W2)
26.5-25	32	1750	675	22.00/3.0	17000	11200	550	425	E3/L3(W1/W2)
29.5-25	28	1875	750	25.00/3.5	17500	11500	425	325	E3/L3(W2)
29.5-25	32	1875	750	25.00/3.5	200000	12950	525	400	E3/L3(W2)
14.00-24	20	1370	375	10.00	8500	4625	700	475	E3/L3(W1)
14.00-24	24	1370	375	10.00	9500	5150	850	575	E3/L3(W1)
14.00-24	28	1370	375	10.00	10000	5600	925	650	E3/L3(W1)
14.00-25	24	1370	375	10.00/1.5	9500	5150	850	575	E3/L3(W1)
14.00-25	28	1370	375	10.00/1.5	10000	5600	925	650	E3/L3(W1)
14.00-25	32	1370	375	10.00/1.5	10900	6150	1050	750	E3/L3(W1)
16.00-24	24	1495	430	11.25/2.0	10600	6000	650	475	E3/L3(W1)
16.00-24	28	1495	430	11.25/2.0	11500	6700	750	575	E3/L3(W1)
16.00-25	28	1495	430	11.25/2.0	11500	6700	750	575	E3/L3(W1)
18.00-25	28	1615	500	13.00/2.5	13600	8000	650	500	E3/L3(W1/W2)
18.00-25	32	1615	500	13.00/2.5	15000	8750	750	575	E3/L3(W1/W2)
18.00-25	36	1615	500	13.00/2.5	16000	9250	850	625	E3/L3(W1/W2)
18.00-25	40	1615	500	13.00/2.5	17000	9700	950	700	E3/L3(W1/W2)



(Off-The-Road) Tyre



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)	Inflated Pressure (kpa)	Pattern
					50 km/h	50 km/h	
825-16	12	855	235	6.50H	650	210	E3/L3(W3)
1200-16	16	840	240	6.50H	1705	680	E3/L3(W3)

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)		Inflated Pressure (kpa)		Pattern
					10 km/h	50 km/h	10 km/h	50 km/h	
23.5-25	20	1615	595	19.50/25	10900	7300	375	300	E3/L3(W3)
23.5-25	24	1615	595	19.50/25	12500	8000	475	350	E3/L3(W3)
17.5-25	16	1350	445	14.00/1.5	7300	4250	475	300	E3/L3(W3)



G2/L2



G2



L4



L5

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)	Inflated Pressure (kpa)	Pattern
					10 km/h	10 km/h	
8.25-16	16	855	235	6.50H	1800	730	G2/L2
17.5-25	16	1400	445	14.00/1.5	7300	475	L4
17.5-25	20	1400	445	14.00/1.5	8250	575	L5
20.5-25	24	1550	520	17.00/2.0	10300	525	L5
23.5-25	24	1675	595	19.50/2.5	12500	475	L5
26.5-25	28	1800	675	22.00/3.00	15500	475	L5
20.5/70-16	16	950	400	8.5H	2850	350	G2
16/70-20	14	1070	410	13	5150	450	G2

OTR TYRE



Grader Loader Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)		Inflated Pressure (kpa)		Pattern
					10 km/h	50 km/h	10 km/h	50 km/h	
1300-24	12	1278	333	8.00TG	5600	2725	450	300	G2/L2
1400-24	16	1348	362	8.00TG	7300	3650	550	350	G2/L2
15.5-25	12	1275	395	12.00/1.3	5600	3250	400	250	G2/L2
17.5-25	16	1350	445	14.00/1.5	7300	4250	475	300	G2/L2
20.5-25	16	1493	521	17.00/2.0	8520	4000	350	225	G2/L2
23.5-25	16	1617	597	19.50/2.5	9500	4750	300	200	G2/L2



Grader Loader Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)	Inflated Pressure (kpa)	Pattern
9.00-20	14	1038	259	7.0	5195	760	G2/L2
10.00-20	16	1073	278	7.5	6085	790	G2/L2



Sand Tyre



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)	Inflated Pressure (kpa)	Pattern
14.00-20	18	1215	332	10.00	4125	245	RST800/RST808 RST818/ RST828
16.00-20TT	18	1330	388	10.00	4350	325	RST828



RST800



RST808



RST818



RST828

Small Trailer Tyre



RST300



RST301



RST302



RST777

Metric Tyre Size	Wheel Diameter (inches)	Load in KG	Load Range Load Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Max PSI LBS rated	Pattern
175/80D	13	615	C	6	610	177	50	RST301
205/75D	14	800	C	6	664	203	50	RST301
205/75D	15	825	C	6	689	203	50	RST300/RST301
225/75D	15	1,150	D	8	719	223	65	RST301
235/80D	16	1,360	E	10	782	236	80	RST301
700-15	15	1,395	E	10	750	200	75	RST302
750-16	16	1,650	F	12	850	215	90	RST302
750-17	17	1,439	F	10	843	212	90	RST777



RST303

Size	PR	Rim	Max Load (IBS)		Inflated Pressure (PSI)		Load Range	Pattern
			Single	Dual	Single	Dual		
100-20	14	7.50	6175	5750	100	90	G	RST303
11-22.5	14	8.25	6175	5750	100	90	G	RST303

Mobile Home Tyre



Wheel Diameter (inches)	Load in Kg	Load Range Load Index	Ply Rating	Overall Diameter	Section Width	Max PSI LBS rated	Pattern
16	1,380	E	14	706	203	90	RST304

TRUCK TYRES



RST501



LUG



RST500



RST502



RIB



RST503

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-13	8	655	170	4.50B	650	420	RST501
6.00-14	8	680	170	4 1/2J	690	420	RST501
6.00-15	8	705	170	4.50E	730	420	RST501
6.50-16	8	750	185	5.50F	850	420	RST501
4.00-12	4	535	110	3.00D	250	340	LUG
4.00-14	4	590	110	3.00D	270	340	LUG
4.00-16	4	640	110	3.00D	300	340	LUG
4.50-14	8	606	122	3.00D	580	520	LUG
4.50-16	6	655	122	3.00D	462	450	LUG
5.00-14	8	628	130	4J	500	420	LUG
5.00-16	6	685	140	4.00E	480	390	LUG
5.50-16	6	710	150	4.00E	525	370	LUG
6.00-16	10	730	170	4.50E	850	530	LUG
7.00-16	10	775	200	5.50F	1090	530	LUG
7.50-16	14	805	215	6.00G	1500	730	LUG
7.50-20	14	935	215	6.0	1900	810	LUG
8.25-16	14	855	235	6.50H	1700	630	LUG
8.25-20	14	974	236	6.5H	2240	810	LUG
9.00-20	16	1018	259	7.0	2900	880	LUG
4.50-12	12	545	127	3.00B	535	550	RST500
6.50-15	8	730	180	4.50E	825	420	RST502
6.50-16	8	750	185	5.50F	850	420	RST502
7.00-16	10	775	200	5.50F	1090	530	RST502
7.50-16	14	805	215	6.00G	1500	730	RST502
6.00-13	8	655	170	4.50B	650	420	RIB
6.00-14	8	680	170	4 1/2J	690	420	RIB
6.00-15	8	705	170	4.50E	730	420	RIB
6.50-14	8	705	180	4 1/2J	775	420	RIB
6.50-16	8	750	185	5.50F	850	420	RIB
7.00-15	10	750	200	5.50F	1030	530	RIB
7.00-16	10	775	200	5.50F	1090	530	RIB
7.50-15	10	780	215	6.00G	1215	530	RIB
7.50-16	14	805	215	6.00G	1500	730	RIB
8.25-16	14	855	235	6.50H	1700	630	RIB
9.00-20	16	1018	239	7.0	2900	680	RIB
7.50-16	14	805	215	6.00G	1500	730	RST503
8.25-16	16	855	235	6.50H	1800	730	RST503



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
7.50-16	14	805	215	6.00G	1500	730	RST506
7.00-16	14	775	200	5.50F	1320	730	RST506
7.00-15	12	750	200	5.50F	1150	630	RST506
6.50-16	12	761	185	5.50F	1060	630	RST505
7.00-16	14	785	200	5.50F	1320	730	RST505
7.50-16	14	816	215	6.00G	1500	730	RST505
8.25-16	16	867	235	6.50H	1800	730	RST505
6.50-16	12	761	185	5.50F	1060	630	RST504
7.00-16	14	785	200	5.50F	1320	730	RST504
7.50-16	14	816	215	6.00G	1500	730	RST504
8.25-16	16	867	235	6.50H	1800	730	RST504
7.50-16	14	816	215	6.00G	1500	730	RST669A
8.25-16	16	867	235	6.50H	1800	730	RST669A
6.00-13	12	655	170	4.50B	825	630	RST702
6.00-14	10	691	170	41/2J	800	530	RST702
7.50-16	16	816	215	6.00G	1650	830	RST702C
9.00-20	16	1038	259	7.0	2900	880	RST702C
10.00-20	18	1073	278	7.5	3350	910	RST702C
11.00-20	18	1105	293	8.0	3650	910	RST702C



RST506



RST505



RST504



RST669A



RST702



RST702C

INDUSTRIAL



R-4(A)



R-4(B)



R-4(C)



R-4(D)



R-1M

Industrial Tractor Tyre (Tubeless)

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
10.5/80-18	10	925	274	9	1935	350	R-4(A)
12.5/80-18	12	985	308	9	2625	370	R-4(A)
16.9-24	12	1309	429	W15L			R-4(B)
16.9-28	12	1410	429	W15L			R-4(B)
17.5L-24	12	1241	445	W15L			R-4(B)
19.5L-24	12	1314	495	DW17			R-4(B)
21L-24	12	1378	533	DW18			R-4(B)
18.4-26	12	1436	467	DW16			R-4(B)
12.5/80-18	12	1001	350	9	2625	370	R-4(C)
16.9-28	12	1435	430	W15L	3450	260	R-4(C)
18.4-26	12	1450	467	DW16L	2985	230	R-4(C)
15.5/80-24 (400/80-24)	12	1240	395	W13	4000	150	R-4(D)
405/70-20 (16/70-20)	14	1075	410	13.0	3750	350	R-1 M
405/70-24 (16/70-24)	14	1175	410	13.0	3950	350	R-1 M
11L-15	10	813	279	8LB	1060	360	F-3
11L-16	12	838	279	8LB	1250	420	F-3
16.9-24	12	1236	429	15	3250	260	RST801
16.9-28	12	1435	430	15	3450	260	RST801
19.5L-24	12	1314	495	17	3455	230	RST801
19.5L-24	12	1314	495	17	3455	230	RST802
12.5/80-18	12	1001	350	9	2625	370	RST803
16.9-28	12	1435	430	15	3450	260	RST803
16.9-24	12	1236	429	15	3250	260	RST804
16.9-28	12	1435	430	15	3450	260	RST804
23.1-26	14	1500	595	DW20	5600	280	R-3



F-3



RST801



RST802



RST803



RST804



R-3



Military Tyre



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
1300X530-533	16	1300	530	440X533	4775	525	E-2

FORKLIFT TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kg)	Inflated Pressure (kpa)	Pattern
5.00-8	10	470	137	3.50D	1150	1000	RST202
6.00-9	10	540	160	4.00E	1505	860	RST202
6.50-10	10	590	175	5.00F	1655	790	RST202
7.00-12	14	676	190	5.00S	2590	1000	RST202
7.00-15	14	750	200	5.5	3140	1000	RST202
7.50-15	14	780	215	6	3375	925	RST202
8.25-15	14	840	235	6.5	3775	830	RST202
18*7-8	14	465	173	4.33R	1505	970	RST202
21*8-9	14	535	200	6.00E	2040	1000	RST202
23*10-12	14	597	254	8.00G	2950	830	RST202
23*9-10	16	595	225	6.50F	2810	1030	RST202
250-15	16	735	250	7.5	3865	930	RST202
27*10-12	14	690	255	8.00G	3285	860	RST202
28*9-15 (8.15-15)	14	706	220	7	3050	970	RST202
300-15	20	840	300	8	5940	930	RST202
10.00-20	16	1055	278	7.5	6030	790	RST202
12.00-20	20	1125	315	8.5	7400	1000	RST202

INDUSTRIAL



Solid Tyre

Size	RIM	Overall Diameter (mm)	Section Width (mm)	Load Capacity (kg) Balance Forklift			Other Forklifts (kg)	Pattern
				10km/h	16km/h	26km/h	16 km/h	
				Drive Steer	Drive Steer	Drive Steer		
4.00-8	3	423	121	1090/840	995/765	925/710	710	RST200
5.00-8	3	469	146	1255/965	1145/880	1060/815	815	RST200
200/50-10	6.5	460	221	2910/2240	2665/2050	2470/1900	1900	RST200
6.00-9	4	545	160	1975/1520	1805/1390	1675/1290	1290	RST200
6.50-10	5	597	178	2715/2090	2485/1910	2310/1775	1775	RST200
7.00-9	5	578	186	2670/2055	2440/1875	2260/1740	1740	RST200
7.00-12	5	683	192	3105/2390	2835/2180	2635/2025	2025	RST200
7.00-15	5.5	759	204	3700/2845	3375/2595	3150/2410	2410	RST200
7.50-15	5.5	774	215	3805/2925	3470/2670	3225/2480	2480	RST200
7.50-16	5.5	820	220	4035/3105	3685/2835	3425/2635	2635	RST200
28*9-15 (8.15-15)	7	706	225	4060/3125	3710/2855	3445/2650	2650	RST200
8.25-12	5	735	236	3425/2635	3125/2405	2905/2235	2235	RST200
8.25-15	5.5	847	236	4305/3310	3925/3020	3640/2800	2800	RST200
8.25-20	6.5	992	236	5165/4305	4715/3930	4380/3650	3650	RST200
9.00-16	6.5	884	259	5290/4070	4830/3715	4485/3450	3450	RST200
9.00-20	7	1038	259	6365/5305	5815/4845	5400/4500	4500	RST200
10.00-20	7.5	1073	278	7075/5895	6460/5385	6000/5000	5000	RST200
11.00-20	7.5	1095	300	7470/6225	6820/5685	6330/5275	5275	RST200
12.00-20	8	1180	310	8640/7200	7885/6570	7320/6100	6100	RST200
21*8-9	6	535	207	2890/2225	2645/2035	2455/1890	1890	RST200
15*4 1/2-8	3	380	114	1005/775	915/705	805/655	655	RST200
16*6-8	4.33	418	162	1545/1190	1410/1085	1305/1005	1005	RST200
18*7-8	4.33	457	170	2430/1870	2215/1705	2060/1585	1585	RST200
23*9-10	6.5	595	225	3730/2870	3405/2620	3160/2430	2430	RST200
23*10-12	8	595	261	4450/3425	4060/3125	3770/2900	2900	RST200
27*10-12	8	683	261	4595/3535	4200/3230	3900/3000	3000	RST200
250-15	7.5	735	250	5595/4305	5510/3930	4745/3650	3650	RST200
300-15	8	838	300	6895/5305	6300/4845	5850/4500	4500	RST200

www.restagro.com.tr

Wechat



Botim



Factory / Usine
Konya Organize Sanayi Bölgesi Kayacık Mh.
T. Ziyaeddin Cd. No:31
Selçuklu / Konya/ TÜRKİYE
info@restagro.com.tr
export@restagro.com.tr
+90 332 501 03 32 / +90 532 113 81 40

Istanbul – Head Office / Istanbul Siege Social
Pınarstepe Mah Yavuz Sultan Selim Bulvarı No:6
Beyaz Plaza kat. 5/45 Büyükcçekmece / İstanbul / TÜRKİYE
info@restagro.com.tr
+90 212 320 42 16 / +90 507 537 18 40

Algeria – Head Office / Algerie Siege Social
Lot. Batiment A N 01 Coop. Batimetal El
Bahdja Rue 1200 Logts. Alger /ALGERIA
+213 542 27 25 08

